



PHONOMAX

Intercom System

www.phonomax.com

System Salient Features

Salient Features

Do not Disturb
Call Privacy
Call Forward
Call Forward on Busy
Follow Me
Call Pick-up
Hotline with Delay
Normal Alarm
Time Slot Alarm
Daily Alarm
Call Waiting Activation with Pick-up
Call Camp-on
Call Parking
Extension Busy Override
Call Interrupt
Vendor Call Request
Denied List Set(10)
Allow List Set(10)

Flash Time
Visitor Double Check
Watchmen Watchdog with Veiw
Paging Access
Smart Switch(3)
Smart Switch Auto Operation
Panic Alert with Message
Panic Hooter
Security Display (8/16)
Society Message Announce or Broadcast (5)
Missed Call Listen(10)
Received Call Listen (10)
Dialled Call Listen(10)
Vendor Arrival Alert(10)
Extension Jack Announce
Extension Number Announce
System Cascading*

System Hardware Configuration

Salient Features

Salient Features

	IX-40	GXI-80	GXI-192
Extension capacity maximum	40	80	192
Intercom Speech Path	7	15	15
Paging port	1	1	1
Maximum Display	8	16	16
Length or Height in cm	21	25	43
Breadth or Width in cm	21	21	21
Depth in cm	11	13	13

System Specifications

- Microcontroller based stored program control
- Extension loop resistance 300R excluding telephone
- Space division switching
- Insertion loss less than 1dB
- Input power 90 to 230V AC 50/60 Hz
- DTMF as per CCITT Q.23
- Cross talk better than 65 dBm
- Battery back-up 12V, 7Amp

Switcher

Maximum System (GXI Only)	16
Maximum port	2700
Maximum Display	16
Speech Path	15
Serial RS-485 Wiring	Loop

Manufactured by: **Phonomax Systems**
Mumbai, INDIA

Marketed by: