



**PHONOMAX**

Hybrid PBX System



## System Salient Features

Sailient Features	Systems	
	PX	NX
Intercom	YES	YES
Call Pick-up	YES	YES
Global Memory (100)	YES	YES
Redial	YES	YES
Access to Trunk Line	YES	YES
Direct Access	YES	YES
Walk-in Class of Service	YES	YES
Dynamic Lock	YES	YES
Call Restriction	YES	YES
Auto Call Disconnecter	YES	YES
Barge-in Level Based	YES	YES
Alarm Normal / Time Slot	YES	YES
Auto Call Back	YES	YES
Call Camp-on	YES	YES
Call Forward	YES	YES
Call Forward on Busy	YES	YES
Call Parking	YES	YES
Call Privacy	YES	YES
Do Not Disturb	YES	YES
Follow Me	YES	YES
Hot Outward Dialing	YES	YES

Sailient Features	Systems	
	PX	NX
Call Transfer	YES	YES
Conference 3-Party	YES	YES
Flexible Numbering	YES	YES
Auto Day/Night Mode	YES	YES
Flexible Ring Assignment	YES	YES
SMDR	YES	YES
External Music	YES	YES
Hybrid Port	NO	YES
Paging Port	YES	YES
Real Time Clock	YES	YES
Battery Backup	YES	YES
CLID DTMF / FSK	YES	YES
Smart Switch *	NO	YES
Flash on Trunk	YES	YES
Key Phone Paging	NO	YES
Key Phone Live Call View	NO	YES
Voice Guidance (DISA) *	YES	YES
Voice Guidance Flexible Parameter	YES	YES
Auto Attendant Two Level *	YES	YES
Trunk Status Display	NO	YES
SMDR View on KTS	NO	YES

## System Specifications

Microcontroller based stored programme control.

Space Division Switching.

Extension Loop Resistance - 250R (excluding telephone).

Insertion Loss less than 1dB.

DTMF dialling as per CCITT Q.23.

Cross Talk better than 65dbm.

I/P Power 85V to 230V AC 50Hz.

Battery 12V 3.5Amp

System Dimension ( 21 x 21 x 8 in cm)

Manufactured by:

**Phonomax Systems**  
Mumbai INDIA

Marketed by:

